


## Technical datasheet Cairsens H2S/CH4S

(Document prone to modifications)

<b>Range</b>	0- 200 ppm (0-190 ppm analog)
Limit of detection <sup>(1, 2)</sup>	200 ppb
Repeatability at zero <sup>(1, 2)</sup>	+/- 200 ppb
Repeatability at 80% of range <sup>(1, 2)</sup>	+/- 15%
Linearity <sup>(1, 2)</sup>	< 10%
Uncertainty	< 30 % <sup>(2, 3)</sup>
Short term zero drift <sup>(1, 2, 4)</sup>	< 50 ppb/24 H
Short term span drift <sup>(1, 2, 4)</sup>	<1% FS <sup>(5)</sup> /24 H
Long term zero drift <sup>(1, 2, 4)</sup>	< 100 ppb/1 month
Long term span drift <sup>(1, 2, 4)</sup>	< 2% FS <sup>(5)</sup> /1 month
Rise time (T10-90) <sup>(1, 2)</sup>	< 120s (180s if large variation RH)
Fall time (T10-90) <sup>(1, 2)</sup>	< 120s (180s if large variation RH)
Effect of interfering species <sup>(1)</sup>	Other VRSC <sup>(6)</sup> (SO <sub>2</sub> , OCS, C <sub>2</sub> H <sub>6</sub> S, C <sub>2</sub> H <sub>6</sub> S <sub>2</sub> , ...): < 100% Oxidant species negative interference (O <sub>3</sub> , NO <sub>2</sub> ) : ~ 30 %
Temperature effect on sensitivity <sup>(2)</sup>	< 0.5 % / °C
Temperature effect on zero <sup>(2)</sup>	+/- 500 ppb maximum under operating conditions
Maximum exposure	500 ppm
Annual exposure limit (1 hour average)	500 000 ppm
Operating conditions	-20°C to 40°C / 15 to 90% RH non-condensing 1013 mbar +/- 200 mbar
Recommended storage conditions	Temperature: between 5°C and 20°C Air relative humidity: > 15% non-condensing
Power supply <sup>(7)</sup>	5 VDC/500mA (rechargeable by USB via PC or 100V-240V/5V 0.8A-1.0A with adapter)
Communication interface	USB, UART Analog (UART & 4-20 mA / 0-5 V converter)
Dimensions	Diameter: 32mm - Length: 62mm
Weight	55g
Protection	IP42 (according IEC60529)
Electrical certification	 Conform to UL Std. 61010-1 Certified to CSA Std. C22.2 N°. 61010-1 
Parameters Set up / Downloading	Software: Cairsoft (for USB versions), Cairmap or Caircloud (for UART versions)

<sup>1</sup> According to our operating conditions during tests in laboratory: 20°C +/- 2°C / 50% RH +/- 10% / 1013 mbar +/- 5%

<sup>2</sup> Values possibly affected by exposures to high gradients of concentration

<sup>3</sup> On the basis of recommendations of the Directive 2008/50/EC of the European Parliament and of the Council of 21 May 2008 on ambient air quality and cleaner air for Europe for and its enlargement to other gases

<sup>4</sup> Full scale continuous exposure

<sup>5</sup> FS = Full Scale

<sup>6</sup> VRSC = Volatile Reduced Sulfur Compounds

<sup>7</sup> The complete discharge of a device (screen turned off) can lead to a deterioration of its performances

Any use of the sensor not complying with the conditions specified in herein, including exposures, even short ones, to environments other than ambient air, to dry and / or devoid of oxygen air or other atmosphere not composed in majority of air, even during calibration, will invalidate the warranty.

<b>Main options</b>	Cairtub: protection for outdoor use and power for 21 days. Cairnet: protection for outdoor use, autonomous power (solar panel) and wireless communication for distant access to data
---------------------	---